

OAK CHAINSAW GLOVES

GLOVES - Ref. GA20 - Size: 8 to 12

EN ISO 21420: 2020

EN ISO 11393-4: 2019 Class 2 (24m/s) Design A Type 2

EN 388: 2016 + A1: 2018 level 3233X




The PPE Specialist

PRODUCT PHOTOS



UNISEX MODEL

Design A



Type 2

DESCRIPTION

The OAK gloves are class 2 (24m/s) design A type 2 chainsaw protection gloves (left hand protection), that promise high resistance with cowhide leather, ultra resistant stitching and artery protection.

3 KEY BENEFITS

- **Class 2 (24m/s) Design A Type 2 protection** (left hand protection).
- High resistance to **tearing** (level 3 out of 4), to **abrasion** (level 3 out of 4), and to **puncture** (level 3 out of 4).
- **Water-repellent cowhide leather palm.**

CARE

Wipe with a dry cloth. Do not wash in washing machine. Store in a dry, ventilated place away from dust and moisture.

PACKAGING

Boxes of 50 pairs.
Sub-packaging: 2 pairs. Single-unit packaging.



OAK CHAINSAW GLOVES

GLOVES - Ref. GA20 - Size: 8 to 12

EN ISO 21420: 2020

EN ISO 11393-4: 2019 Class 2 (24m/s) Design A Type 2

EN 388: 2016 + A1: 2018 level 3233X

For resellers,
order on B2B



TECHNICAL SPECS



Stretch fabric 97% Polyamide /
3% Elasthane

Rib-knit cuff

Reinforced Palm

Leather artery
protection

GENERAL REQUIREMENTS EN ISO 21420



General requirements relating to glove design and construction, safety, comfort and dexterity, as well as marking and information provided by the manufacturer applicable to all protective gloves.

COMPLIANCE



PPE Cat. III

0598/PPE/23/4357/R
Issued by notified body 0598

EN ISO 11393-4: 2019



Class 2
Design A

MECHANICAL RISKS EN 388



Abrasion (number of cycles required for the abrasive paper to pass through the fabric or leather). Level 1 to 4.



Cut resistance EN 388: 2003 (index - compared to a standardized fabric at constant pressure and speed, the number of cycles with a circular blade to cut the material). Level 1 to 5.



Tear resistance (force required in Newtons to tear the material). Level from 1 to 4.



Perforation (force required in Newtons for a punch to pass through the glove). Level 1 to 4.



ISO 13997 **cut** (force required in Newtons for a razor blade to cut through the material over a 20 mm distance). Level from 0 to F. Test not performed = X.



Impact (maintaining the integrity of the glove following a drop of 2.5 kg with an energy of 5 joules). Success = P.

RESULTS

- Certified Class 2 (24m/s) Design A Type 2
- Certified level 3233X

EN 388: 2016
+A1: 2018



3233X



SOLIDUR SAS

335, Impasse Teractive Ouest - ZA Teractive - 50140 Romagny-Fontenay, FRANCE

Tel. +33 (0)2 33 59 45 12

www.solidur.fr @solidur1946





EN

DECLARATION OF CONFORMITY

The manufacturer,
SOLIDUR
355 Impasse Teractive Ouest - ZA Teractive 50140 Romagny-Fontenay - FRANCE
Tel. +33 (0)2 33 59 45 12

Declares that the product: **Chainsaw protective gloves**

Reference: **GA20 (HG-PCG24MS)**

Brand: **SOLIDUR®**

Complies with EU harmonisation legislation: EU Regulation **2016/425**

and standard(s):
EN ISO 21420: 2020
EN 388: 2016 + A1: 2018 (Level 3233X)
EN ISO 11393-4: 2019 CLASS 2 DESIGN A TYPE 2

This product has undergone an EU type-examination (module B)
with the issue of EU type-examination certificate n°
0598/PPE/23/4357 Issue 1

Issued by:
SGS Fimko Ltd
Notified Body 0598
Takomotie 8
FI-00380 Helsinki
FINLAND

Romagny-Fontenay,
Date: 13/11/2024

Anthony LE BIGOT, PDG

Find the declaration of conformity for your PPE on conformity.solidur.fr

SAS SOLIDUR 355 Impasse Teractive Ouest - ZA Teractive 50140 Romagny-Fontenay - FRANCE
Siret 32370593900045 - Tel. +33 (0)2 33 59 45 12 - Fax. +33 (0)2 33 59 99 04
contact@solidur.fr - www.solidur.fr

